

TO
TAL
LY
HA
PPY



AVAILABLE IMMEDIATELY! ▶ **to go**

WITH THE TS 200 SD P

The complete package: Double grinding machine TS 200 SD P

with brake, EMERGENCY STOP button and machine stand with integrated suction system

- ▶ Standard equipment
- ▶ Smooth, no-maintenance motor
- ▶ Protective hood closed at the sides
- ▶ Stable workpiece supports that can be adjusted
- ▶ High level of safety thanks to adjustable spark deflector
- ▶ Suitable for grinding, deburring and sharpening tools of all kinds, metal profiles etc.
- ▶ Circuit breaker and under-voltage release
- ▶ Spark/eye protection on both sides
- ▶ Connecting cable with CEE plug 16 A
- ▶ Coarse and fine for each grinding wheel
- ▶ Machine stand with submersible container, Dimensions: 355 x 300 mm, Weight: 12 kg
- ▶ Dust extraction system MA 400 D
- ▶ EMERGENCY STOP BUTTON and brake
- ▶ 12-month warranty for single-shift operation

**ONE NUMBER WITH
EVERYTHING INCLUDED!**
Order number 317.777

You can find out more about
TS 200 SD P on Page 82/83
in our catalogue!

Double grinding machine

TS 175 Pro

TS 200 Pro

TS 250 Pro



Fig.: TS 200 Pro with machine stand, EMERGENCY STOP button, brake and suction system

Standard equipment

- ▶ Smooth, no-maintenance motor
Operating type S1 (continuous operation)
- ▶ Protective hood closed at the sides
- ▶ Stable workpiece supports that can be adjusted
- ▶ High level of safety thanks to adjustable spark deflector
- ▶ Suitable for grinding, deburring and sharpening tools of all kinds, metal profiles etc.
- ▶ Circuit breaker and under-voltage release
- ▶ Spark/eye protection on both sides
- ▶ Connecting cable with CEE plug 16 A
- ▶ Coarse and fine for each grinding wheel
- ▶ 12-month warranty for single-shift operation
- ▶ **Available optionally***
Complete with EMERGENCY STOP button and brake!
(Only in combination with machine stand or suction system)

Special equipment

- ▶ With machine stand, EMERGENCY STOP button and brake*
Order number for TS 175: 317.841
Order number for TS 200: 317.846
Order number for TS 250: 317.851
- ▶ With machine stand, EMERGENCY STOP button, brake and suction system*
Order number for TS 175: 317.842
Order number for TS 200: 317.847
Order number for TS 250: 317.852
- ▶ different colour shade
(One-component RAL paint)
Order number 309,010
- ▶ Foot switch emergency stop
(can only be ordered in connection with brake, machine stand and/or suction system)
Order number 317.859

Accessories

- ▶ Separate spare grinding wheel
Normal corundum coarse
Order number for TS 175: 317.526
Order number for TS 200: 317.532
Order number for TS 250: 317.542
- ▶ Separate spare grinding wheel
Normal corundum fine
Order number for TS 175: 317.527
Order number for TS 200: 317.533
Order number for TS 250: 317.543
- ▶ Dressing stone
Order number 350.101
- ▶ Machine stand with submersible container,
Dimensions: 355 x 300 mm, Weight: 12 kg
(only TS 175 Pro / TS 200 Pro)
Order number 350.435

Technical data

Suction piece Ø (mm)	42
TS 175 Pro	
Dimensions of the grinding wheel (mm)	175 x 25 x 32
Machine dimensions without VP (mm)	230 x 440 x 210
Machine dimensions with VP (mm)	260 x 450 x 250
Speed (1/min)	2,750
Motor three-phase current 400 V (kW)	0.7, S1 (continuous operation)
Weight (kg)	15
Order number	317.840
TS 200 Pro	
Dimensions of the grinding wheel (mm)	200 x 32 x 32
Machine dimensions without VP (mm)	250 x 470 x 230
Machine dimensions with VP (mm)	300 x 480 x 275
Speed (1/min)	2,550
Motor three-phase current 400 V (kW)	0.75, S1 (continuous operation)
Weight (kg)	20
Order number	317.845
TS 250 Pro	
Dimensions of the grinding wheel (mm)	250 x 40 x 51
Machine dimensions without VP (mm)	280 x 530 x 270
Machine dimensions with VP (mm)	325 x 540 x 310
Speed (1/min)	1,400
Motor three-phase current 400 V (kW)	0.8, S1 (continuous operation)
Weight (kg)	32
Order number	317.850

- ▶ Machine stand
(only TS 250 Pro)
Order number 350.436
- ▶ Dust extraction system MA 400 D
(only for TS 175 Pro / TS 200 Pro)
Order number 330.295
- ▶ Dust extraction system MA 600 D
(only for TS 250 Pro)
Order number 330.080

Combined
belt sander/
grinding machine
TSB 250 P



AVAILABLE
IMMEDIATELY! **to go**

Fig.: TSB 250 P with machine stand

Standard equipment

- ▶ High performance
- ▶ Belt sanding equipment, height-adjustable, 0-90°
- ▶ Maximum useable surface grinding area
- ▶ Belt adjustment with fine tuning
- ▶ Longitudinal stop for material guiding
- ▶ Perfectly balanced and low vibration
- ▶ Connection for dust extraction Ø 50 mm on both sides
- ▶ Circuit breaker with under-voltage release
- ▶ Fixed stop
- ▶ 1 standard grinding belt (below), grain 80
- ▶ 1 grinding wheel 250 x 40 x 51 mm, grain 80
- ▶ Spark arrester
- ▶ Connecting cable with CEE plug
- ▶ 12-month warranty for single-shift operation

Special equipment

- ▶ With machine stand, EMERGENCY STOP button and brake*
Order number 330.365
- ▶ With machine stand, EMERGENCY STOP button, brake and suction system*
Order number 330.370

Accessories

- ▶ Grinding wheel 250 x 40 x 51 mm
Grain 36 coarse
Order number 317.542
- ▶ Grinding wheel 250 x 40 x 51 mm
Grain 80 fine
Order number 317.543
- ▶ Standard grinding belt (brown) 1,300 x 75 mm, 5 pieces, grain 40
Order number 316.042
- ▶ Standard grinding belt (brown) 1,300 x 75 mm, 5 pieces, grain 80
Order number 316.041
- ▶ Graphite coating 80 x 350 mm
Order number 316.045
- ▶ Machine stand with submersible container
Order number 350.436
- ▶ Machine stand with integrated dust suction system (MA 600)
Order number 330.080

Technical data

TSB 250 P

Dimensions of the grinding wheel (60 grain) (mm)	250 x 40 x 51
Machine dimensions without VP (mm)	600 x 320 x 700
Machine dimensions with VP (mm)	650 x 800 x 350
Speed (1/min)	1,400
Weight (kg)	35
Belt speed (m/s)	15
Band dimensions (mm)	1,300 x 75
Grain size	80
Sound level [dB (A)]	78
Motor three-phase current 400 V (kW)	1.4
Measurement with grinding arm position (vertical) (mm)	560 x 320 x 680
Order number	330.360
Additional accessories	from Page 100